







# Mounting Base for UL 489 Multi 9 C60

## Specifications

<b>Ratings</b>	UL recognized for use with UL 489 Multi 9 C60 miniature circuit breakers per UL 67, CSA C22.2 #29 and IEC 60439-1 Also CE marked
<b>Voltages</b>	240 Vac and 125 Vdc
<b>Ampacity</b>	200 A maximum (see table on page two)
<b>Interrupting Rating</b>	10 kA @ 0.05 seconds
<b>Conductors/Bus</b>	1, 2 and 3 conductors; suitable for use with 1, 2 and 3 pole circuit breakers
<b>Pole Capacity</b>	12, 24, 36, 48, 60
<b>Branch Breakers</b>	UL 489 C60 with 18 mm spacing (future option for C120 with 27 mm spacing and combination of C60/C120)
<b>Input Terminal</b>	One-inch wide 1/4-20 x 1-inch studs with nuts/washers for compression ring lugs, bus bar or optional lugs
<b>Optional Lug Kit</b>	Catalog number USMBLK. Includes one bolt-on lug and one nut/washer for #6 AWG to 300 kcmil cable (same as QOL225 cable lug)
<b>Optional Terminal Cover</b>	Catalog number USMBTC. Provides IP20 ingress protection per IEC 60529; suitable for jumper bars or cables

### Schneider Electric - North American Operating Division

1415 S. Roselle Road  
Palatine, IL 60067  
Tel: 847-397-2600  
Fax: 847-925-7500